



Trimmer



TR250



Scarifying machines
Fraiseuses *Scarificatrici*
Frezarka *Fresadoras*



TRIMMER SRL - VIA PIAVE, 47 Z.I. 26843 CASTELNUOVO B.D'A. (LODI) - ITALY
Tel. +39 0377 700125 Fax +39 0377 60681 - +39 0377 702614 -
e-mail: trimmer@trimmer.it - www.trimmer.it

DATOS TÉCNICOS FRESADORA TR250

	TR250E trifásica 400 V	TR250B gasolina
Ancho de Trabajo	250 mm	250 mm
Distancia de pared a marca fresado	80 mm	80 mm
Anchura	475 mm	475 mm
Longitud	970 mm	970 mm
Altura	1150 mm	1150 mm
Racord tubo de aspiración	Ø 40/50 mm	Ø 40/50 mm
Peso sin tambor de fresas	95 kg	98 kg
Motor	Eléctrico Trifásico	Gasolina
Potencia	4 kW	6,6 kW
Velocidad de giro	2885 R.P.M.	3600 R.P.M.
Alimentación	400 V 16 A	Gasolina sin plomo
Aspirador aconsejado	≥ 2 kW	≥ 2 kW

SPECIFICATIONS SCARIFYING MACHINE TR250

	TR250E three phase 400 V	TR250B gasoline
Working width	250 mm	250 mm
Distance to wall	75 mm	75 mm
Width	475 mm	475 mm
Length	970 mm	970 mm
Height	1150 mm	1150 mm
Connection to vacuum	Ø 40/50 mm	Ø 40/50 mm
Weight without drum	95 kg	98 kg
Engine	Electric three phases	Honda petrol engine
Power	4 kW	6,6 kW
RPM	2885 RPM	3600 RPM
Feed	Electric three phases 400V 16A	Lead free petrol
Recommended vacuum	≥ 2 kW	≥ 2 kW

DATI TECNICI SCARIFICATRICE TR250

	TR250E trifase 400 V	TR250B benzina
Larghezza di lavoro	250 mm	250 mm
Distanza parete-traccia scarificatrice	75 mm	75 mm
Larghezza	475 mm	475 mm
Lunghezza (escluso manico regolabile)	970 mm	970 mm
Altezza (escluso manico regolabile)	1150 mm	1150 mm
Raccordo di aspirazione	Ø 40/50 mm	Ø 40/50 mm
Peso senza tamburo	95 kg	98 kg
Motorizzazione	Elettrica trifase	A scoppio Honda
Potenza	4 kW	6,6 kW
Giri del motore	2885 giri/min	3600 giri/min
Alimentazione	Elettrica trifase 400 V 16 A	Benzina senza piombo
Aspiratore consigliato	≥ 2 kW	≥ 2 kW